## RESIDENTIAL SECURITY SURVEY CONFIDENTIAL

## **AGENCY:**

NAME:ADDRESS:										CASE NO: DATE SURVEYED: TIME:						
PHONE:										CONDUCTED BY:						
										TYPE: ☐ Requested ☐ Canvass ☐ Follow-up						
	TYPE OF CONSTUCTION:  Frame Masonry  TYPE OF CONSTUCTION:  Frame Masonry										☐ Resurvey LAST SURVEY DATE:					
	TYPE OF PREMISES:  Single Family  Apartment  Duplex/Townhouse										PREVIOUS BURGLARIES: ☐ Yes ☐ No DATES:					
П	□ Mobile/Modular Home □ Other										ALARM SYSTEM IN USE:  Yes  No					
ME	MEMBER OF NEIGHBORHOOD WATCH: ☐ Yes ☐ No										TYPE: ☐ Central Station ☐ Stand Alone					
	The purpose of this survey is to provide security recommendations. This report is only advisory and i the adequacy of all present and future security measures whether or not recommended.											not intended to identify all security weaknesses or to warrant				
	-		-	•				DOOR SYSTEMS								
1.	1. HINGED DOORS - F (front) S (side) R (rear) O (other)							2. SLIDING DOORS				3. GARAGE DOORS				
F	s	R	0	Recommendations		Recommendations					□ Exterior					
				Replace with solid door	a. D Pin doors						Overh	nead				
				Reinforce frame and strike	einforce frame and strike plate			b.   Take up slack (spacer in upper track)				Interio	or			
				Cylinder style dead bolt		C.		Use Charlie bar or sim	ilar de	evice	E	0	I	Recommendations		
				Install 180° peephole		d.		Add auxiliary locks						Add auxiliary lock		
				Modify hinges	OTHER								Pin track			
				Install 180° door viewer									Install electric door opener			
	□ □ □ Double door – install lever extension flush bolts									OTHER						
OTHER																
					ows				1		MI	SCELLA	NEOUS	OPENINGS		
4.	DOUE	BLE HU			7. CASE		10. 🗅				Trim shrubbery from window/doors					
a.								Recommendations Pin in locking handle				☐ Address numbers ☐ Locks on gates				
b. c.		☐ Install auxiliary locks b. ☐ Secure a/c unit from inside c. ☐						Keep tightly closed Replace/adjust locking mechanism				<ul> <li>□ Detached buildings</li> <li>□ Misc. Opening (</li></ul>				
5.	SLIDI	NG			8. AWNIN	<b>G</b>				□ O <sub>1</sub>	peration	I.D. (En	grave pro	perty)		
a.				ndations	a. 🗆		Recommendations (spec Remove crank				cify)					
b.		☐ Install anti-slide block b. ☐						14 11 11 1								
C.		☐ Install spacer in upper-track  9. OTHER						· · · · · · · · · · · · · · · · · · ·				Lighting				
6.	JALOUSIE Recommendations										Recommendations					
a. b.	Bar or grill work					a. b.					xterior – . terior – l		al lighting •	I		
. , , , ,												See comments				
OTHER INFORMATION/EXPLANATION OF ABOVE																